

ECOSOFT PROFESSIONAL MO6500 4" REVERSE OSMOSIS SYSTEM



Ecosoft reserves the right to amend the product's system architecture provided that its functionality and usability will not deteriorate

PHYSICAL PARAMETERS

Influent water, concentrate, permeate	G 1/2"
Antiscalant dosing port	G 1/2"
Permeate flushing input port	G 1/2"
Approximate weight (bare system / crated system)	55 kg / 80 kg
Dimensions (bare system, W x D x H)	0.54 x 0.39 x 1.45 m
Dimensions (crate, W x D x H)	0.60 x 0.45 x 1.55 m

ADVANCED ECOSOFT MO6500 4" REVERSE OSMOSIS SYSTEM

Code	Product	Flow rate, L/h (GPH)	Membrane*	Pieces on pallet
MO6500TP5	Ecosoft MO6500 RO System	200-300 (50-80)	1/40 x 40	4

* Membranes are not included in the package

APPLICATIONS

Steam boilers, heating and cooling circuits, breweries and beverage production, livestock and poultry farms, glazing factories, laundry and car wash etc.

KEY FEATURES

- Ecosoft controller OC5000
- Easy to use thanks to smart architecture
- Modularized architecture for adding permeate flushing or raw water blending assembly to the system
- Grundfos worldwide guaranty
- CE marked and confirmed to be safe in accordance with EC New Approach Directives

EQUIPMENT:

- Grundfos® CM 1-10 pump
- 300 psi membrane housing
- BB20 sediment prefilter
- Electrical panel with Ecosoft controller
- Danfoss solenoid valves
- Piping, instrumentation
- Steel frame
- Carton box
- PP melt blown sediment filter, 5 micron

OPTION:

- Filmtec™ XLE-4040 / LCLE-4040 or Ecosoft ELP-4040 membrane
- Dosing pump for antiscalant
- Versatile set for raw water blending (30...240 L/h) or permeate flushing


TECHNICAL SPECIFICATION

Permeate capacity ¹	250 L/h
Permeate recovery ²	75%
Maximum TDS	300 mg/L (10 g/L)
Influent flow demand	320...400 L/h (service) 1500...2000 L/h (rinse)
Operating pressure	8...12 bar
Maximum pressure	14 bar
Electrical requirements	230 V, 50 Hz (1 ph)
Electrical power	0.67 kW
Prefilter rating	5 µm

¹ depends on feed water TDS, temperature, and permeate recovery — see graph on the right

² for low scaling/fouling water

ECOSOFT MO6500 FLOW CAPACITY (WITH XLE-4040 MEMBRANES)



Permeate flow rates are calculated under the following conditions:

- 2 bar influent water pressure
- 0 bar backpressure in the permeate line
- fresh membranes
- XLE-4040 membranes

PIPES AND INSTRUMENTS DIAGRAM

