

STANDARD PRO REVERSE OSMOSIS FILTER WITH MINERALIZATION



KEY FEATURES

- Safe water with mineralization: removes 99.8% of PFAS, bacteria, heavy metals, chlorine.
- 5 stages of water purification including mineralization
- Best-in-class water savings: up to 35% recovery — minimal water waste.
- Certified & trusted: ACS certified, good quality and safe components, backed by decades of Ecosoft experience.
- Enjoy easy maintenance with quick cartridge replacement and no complicated flushing required.
- The filter includes safety features such as a leak sensor and a pressure reducer for reliable operation.

FILTRATION TECHNOLOGY:

- 5 micron PP sediment filter
- AquaGreen filter
- 1 micron sediment PP filter
- 50 GPD RO membrane element
- Mineralizing postfilter

SPECIFICATION:

Code	Flow capacity, LPD (GPD)	Inlet pressure, bar (psi)	Connections	Total volume of storage tank, L (gal)	Dimensions, H x W x D, mm (in)
MO550MECOSTD	190 (50)	3-6 (43.5-87)	1/2", 3/8"	12 (3.2)	414 x 422 x 135 (16.5 x 16.1 x 5.9)

COMPONENTS:

- Filter housing
- Ecosoft pack of pre-filters for reverse osmosis filter
- Membrane element 50 GPD (190 LPD)
- Ecosoft mineralizing postfilter
- Chrome ball valve faucet for purified water
- Plastic pressure tank (total vol. 12 L/3.2 gal, usable vol. up to 7 L/1.8 gal) and tank valve
- Feed water adapter, feed valve, drain saddle
- Pack of color tubes (4 pcs.) for convenient filter installation
- Leak sensor
- Pressure reducer
- Service wrench
- User manual

Unit weight (net/gross), kg: 8.08/9.12

lb: 17.64/19.84

Box dimensions, m: 0.51 x 0.52 x 0.27

in: 20.1 x 20.5 x 10.6

ECOSOFT STANDARD PRO REVERSE OSMOSIS FILTER WITH MINERALIZATION

Code	Product	Pieces in box	Boxes on pallet	Pieces on pallet
MO550MECOSTD	Standard PRO reverse osmosis filter with mineralization	1	24	24

Minimum order is 1 pallet of any product

Make sure to install a pressure reducer before the filter!