

ECOSOFT AQUAPOINT STEEL DUO

Designed for small houses and cottages with 1–2 bathrooms. The Aquapoint Steel provides two-stage mechanical filtration for well water. It effectively removes sand, rust, and sediment, protecting your plumbing and appliances from premature wear while ensuring clear water flow throughout the house.

WATER SOURCE: Well or Rain water supply



KEY FEATURES

- **Heavy-Duty Steel Rack:** Pre-mounted on a solid steel rack for a hassle-free setup. It absorbs pressure vibrations and stays rock-solid on the wall, so you can swap cartridges with ease without worrying about the mount.
- **Maximum Flow Rate:** Large filtration area ensures full water pressure throughout the house, even during peak loads.
- **Double Seal Safety:** Two sealing rubber bands instead of one. This provides double protection against leaks, even if one of them wears out over time.
- **Perfect Alignment:** A special guide inside the head automatically centers the cartridge. Eliminates replacement errors — the cartridge always fits perfectly into place.



The product is completed:

- PP melt blown sediment filter, 4.5"×20", 20 micron
- PP melt blown sediment filter, 4.5"×20", 5 micron
- Service wrench
- 2 quick-connect nipples

OPTIONS

	Step 1	Step 2
Sand and rust	DGD-PP 20/5 CPV452020ECO	PP5 CPV45205ECO
Sand and chlorine	DGD-PP 20/5 CPV452020ECO	GAC CHV4520ECO
Sand and H ₂ S (hydrogen sulfide)	DGD-PP 20/5 CPV452020ECO	GAC-CAT CPVS4520ECO
Sand and iron	DGD-PP 20/5 CPV452020ECO	FERROMIX CRVF4520ECO

TECHNICAL SPECIFICATION

	AQPDOU
Maximum flow capacity, m ³ /hour	1.8
Connection	1" internal thread
Working temperature, °C	+5...+40
Operating pressure, bar	2.0-6.0
Cartridge size	4.5" x 20"